

A Novel Approach to 2D-DCT & 2D-DWT Based JPEG Image Compression

Priyanka Singh Tejyan

Department of Electronics & Communication Engg.
Research Scholar, Amity University
Gurgaon, Haryana
priyanka10ec@gmail.com

Priti Singh

Department of Electronics & Communication Engg
Professor, Amity University
Gurgaon, Haryana
pritip@rediffmail.com

Abstract— Image compression using wavelet transforms results in an improved compression ratio. Wavelet transformation is the technique that provides both spatial and frequency domain information. These properties of wavelet transform greatly help in identification and selection of significant and non-significant coefficients amongst the wavelet coefficients. DWT (Discrete Wavelet Transform) represents image as a sum of wavelet function (wavelets) on different resolution levels. So, the basis of wavelet transform can be composed of function that satisfies requirements of multiresolution analysis. The choice of wavelet function for image compression depends on the image application and the content of image. A review of the fundamentals of image compression based on wavelet is given here. This study also discussed important features of wavelet transform in compression of images. In this study we have evaluated and compared discrete cosine Transform (DCT) & three different wavelet families i.e. Daubechies, Coiflets, Biorthogonal. Image quality is measured, objectively using peak signal-to-noise ratio, Compression Ratio and subjectively using visual image quality.

Keywords-component; DCT, wavelets, wavelet transform, Image compression, compression performance, image quality.

I. INTRODUCTION

A typical still image contains a large amount of spatial redundancy in plain areas where adjacent picture elements i.e. the pixels have almost the same values. It means that the picture elements are highly correlated. The redundancy can be removed to achieve compression of the image data i.e., the fundamental components of compression are redundancy and irrelevancy reduction. The basic measure of the performance of a compression algorithm is the compression ratio, which is defined by the ratio between original data size and compressed data size. Higher compression ratios will produce lower image quality and the vice versa is also true.

Current standards for compression of images use DCT [2-4], which represent an image as a superposition of cosine functions with different discrete frequencies. The transformed signal is a function of two spatial dimensions and its components are called DCT coefficients or spatial frequencies. DCT coefficients measure the contribution of the cosine functions at different discrete frequencies. DCT provides excellent energy compaction and a number of fast algorithms exist for calculating the DCT. Most existing compression systems use square DCT blocks of regular size. The

image is divided into blocks of samples and each block is transformed independently to give coefficients. To achieve the compression, DCT coefficients should be quantized. The quantization results in loss of information, but also in compression. Increasing the quantizer scale leads to coarser quantization, gives high compression and poor decoded image quality. The use of uniformly sized blocks simplified the compression system, but it does not take into account the irregular shapes within real images. The block-based segmentation of source image is a fundamental limitation of the DCT-based compression system. The degradation is known as the "blocking effect" and depends on block size. A larger block leads to more efficient coding, but requires more computational power. Image distortion is less annoying for small than for large DCT blocks, but coding efficiency tends to suffer. Therefore, most existing systems use blocks of 8X8 or 16X16 pixels as a compromise between coding efficiency and image quality.

Wavelets provide good compression ratios, especially for high resolution images. Wavelets perform much better than competing technologies like JPEG 10 both in terms of signal-to-noise ratio and visual quality. Unlike JPEG, it shows no blocking effect but allow for a graceful degradation of the whole image quality, while preserving the important details of the image. The next version of the JPEG standard i.e. JPEG 2000 will incorporate wavelet based compression techniques. In a wavelet compression system, the entire image is transformed and compressed as a single data object rather than block by block as in a DCT-based compression system. It allows a uniform distribution of compression error across the entire image. It can provide better image quality than DCT, especially on a higher compression ratio. However, the implementation of the DCT is less expensive than that of the DWT. For example, the most efficient algorithm for 2-D 8X8 DCT requires only 54 multiplications, while the complexity of calculating the DWT depends on the length of wavelet filters. A wavelet image compression system can be consists of wavelet function, quantizer and an encoder. In our study, we used various wavelets for image compression on image test set and then evaluate and compare the wavelets. According to this analysis, we show the choice of the wavelet for image compression taking into account objective image quality measures [5].

II. IMAGE COMPRESSION USING 2D-DCT

Discrete cosine transform (DCT) is widely used in image processing, especially for compression. Some of the applications of two-dimensional DCT involve still image compression and compression of individual video frames, while multidimensional DCT is mostly used for compression of video streams. DCT is also useful for transferring multidimensional data to frequency domain, where different operations, like spread spectrum, data compression, data watermarking, can be performed in easier and more efficient manner. A number of papers discussing DCT algorithms are available in the literature that signifies its importance and application.

2.1 The Two-Dimensional DCT

The objective of this document is to study the efficacy of DCT on images. This necessitates the extension of ideas presented in the last section to a two-dimensional space. The 2-D DCT is a direct extension of the 1-D case and is given by

$$C(u,v)=\alpha(u)\alpha(v)\sum_{x=0}^{N-1}\sum_{y=0}^{N-1}f(x,y)\cos\left[\frac{\pi(2x+1)u}{2N}\right]\cos\left[\frac{\pi(2y+1)v}{2N}\right]$$

Where $u, v=0, 1, 2, N-1$. (1)

The inverse transform is defined as

$$f(x,y)=\sum_{u=0}^{N-1}\sum_{v=0}^{N-1}\alpha(u)\alpha(v)C(u,v)\cos\left[\frac{\pi(2x+1)u}{2N}\right]\cos\left[\frac{\pi(2y+1)v}{2N}\right]$$

Where $x, y=0, 1, 2, N-1$. (2)

The 2-D basis functions can be generated by multiplying the horizontally oriented 1-D basis functions with vertically oriented set of the same functions.

The following is the general overview of the procedure of Image Compression using DCT process.

1. The image is broken into 8*8 blocks of pixels.
2. Working from left to right, top to bottom, the DCT is applied to each block.
3. Each block is compressed through quantization.
4. The array of compressed blocks that constitute the image is stored in a drastically reduced amount of space.
5. When desired the image is constructed through decompression, a process that uses the Inverse Discrete Cosine Transform (IDCT).

III. DISCRETE WAVELET TRANSFORM

The transform based coding techniques work by statistically de-correlating the information contained in the image so that the redundant data can be discarded [5]. Therefore a "dense" signal is converted to a "sparse" signal and most of the information is concentrated on a few significant coefficients. The greatest problem associated with the transform coding techniques such as DCT based image compression [6] is the presence of visually annoying "blocking artifact" in the compressed image. This has caused an inclination towards the use of

Discrete Wavelet Transform (DWT) for all image and video compression standards. DWT offers adaptive spatial-frequency resolution (better spatial resolution at high frequencies and better frequency resolution at low frequencies). In present scene, much of the research works in image compression have been done on the Discrete Wavelet Transform. DWT now becomes a standard tool in image compression applications because of their data reduction capabilities. The basis of Discrete Cosine Transform (DCT) is cosine functions while the basis of Discrete Wavelet Transform (DWT) is wavelet function that satisfies requirement of multi-resolution analysis. Discrete wavelet transform have certain properties that makes it better choice for image compression. It is especially suitable for images having higher resolution. DWT represents image on different resolution level i.e., it possesses the property of Multi-resolution. Since, DWT can provide higher compression ratios with better image quality due to higher de-correlation property. Therefore, DWT has potentiality for good representation of image with fewer coefficients. DWT Converts an input series x_0, x_1, \dots, x_m , into one high-pass wavelet coefficient series and one low-pass wavelet coefficient series (of length $n/2$ each) given by:

$$H_1=\sum_{m=0}^{K-1}x_{2i-m}\cdot s_m(z) \quad (3)$$

$$L_1=\sum_{m=0}^{K-1}x_{2i-m}\cdot t_m(z) \quad (4)$$

Where $S_m(z)$ and $t_m(z)$ are called wavelet filters, K is the length of the filter, and $i=0, \dots, [n/2]-1$.

In practice, such transformation will be applied recursively on the low-pass series until the desired number of iterations is reached.




Figure. 1 Filter Iteration Series

IV. IMAGE COMPRESSION USING 2D-DWT

A wavelet image compression system can be created by selecting a type of wavelet function, quantizer, and statistical coder. In this paper, we do not intend to give a technical description of a wavelet image compression system. We used a few general types of wavelets and compared the effects of wavelet analysis and representation, compression ratio, image content, and resolution to image quality. According to this analysis, we show that searching for the optimal wavelet needs to be done taking into account not only objective picture quality measures, but also subjective measures. We highlight the performance gain of the DWT over the DCT.

The choice of wavelet function is crucial for performance in image compression. There are a number of basis that decides the choice of wavelet for image compression. Since the wavelet produces all wavelet functions used in the transformation through translation and scaling, it determines the characteristics of the resulting wavelet transform. Therefore, the details of the particular application should be taken into account and the appropriate wavelet should be chosen in order to use the wavelet transform effectively for image compression. The compression performance for images with different spectral activity will decides the wavelet function from wavelet family. In our experiment multiple wavelet functions of wavelet families are examined namely: Daubechies, bior, & Coiflet. Daubechies wavelets are the most popular wavelets. Biorthogonal wavelets, exhibits the property of linear phase, which is needed for signal and image reconstruction. Coiflets are discrete wavelets designed by Ingrid Daubechies. The wavelet is near symmetric their wavelet functions have $N/3$ vanishing moments. The coif_N are much more symmetrical than the db_N s where N is the order of family. By using two wavelets, one for decomposition and the other for reconstruction. This property is used, connected with sampling problems, when calculating the difference between an expansion over the of a given signal and its sampled version instead of the same single one, interesting properties can be derived A major disadvantage of these wavelets is their asymmetry, which can cause artifacts at borders of the wavelet sub bands. The wavelets are chosen based on their shape and their ability to compress the image in a particular application.

V. PERFORMANCE EVALUATION METHODOLOGY

The performance of image compression techniques are mainly evaluated by the two measures: Compression Ratio (CR) and the magnitude of error introduced by the encoding.

The compression ratio is defined as:

$$CR = \frac{\text{The number of bits in the original image}}{\text{The number of bits in the compressed image}}$$

For error evaluation, two error metrics are used to compare the various image compression techniques: Mean Square Error (MSE) and the Signal to Noise Ratio (SNR). SNR is used to measure the difference between two images. In order to quantitatively evaluate the quality of the compressed image the Signal-to-Noise Ratios (SNR) of the images are computed. SNR provides a measurement of the amount of distortion in a signal [4], with a higher value indicating less distortion. For n -bits per pixel image, SNR is defined as:

$$SNR = 20 \log \log_{10} \frac{2^n}{MSE} \quad (5)$$

VI. EXPERIMENT RESULTS & DISCUSSIONS

We also are presenting compression results of test images in terms of visual quality for different wavelet functions for wavelet Families. This analysis presents an analysis and comparison of Image Compression using DCT & DWT. In Image Compression using DWT various wavelet families are used for compressing images.

A. Image Compression Using DCT

Image Compression Using DCT depends upon the no of coefficients where higher no of coefficient generate higher signal to noise ratio and image quality. The discrete cosine transform (DCT) is the basis for many image compression algorithms. One advantage of the DCT over the DFT is that there is no need to manipulate complex numbers. Image Compression using DWT has various advantages over DCT [8]. In case of image compression DWT no need to divide the input coding into non-overlapping 2-D blocks, it has higher compression ratios avoid blocking artifacts. Also allows good localization both in time and spatial frequency domain...When compressed using DCT image quality is improved which is as shown in the results (Fig 2) & graph of No of Coffs for the restored image verses signal to noise ratio is shown in fig 3.




Figure 2. Original Image & restored image of various coefficients.




Figure 3. SNR Graph of the above figure.




Figure 4. SNR & CR of cell image for biorthogonal, Coiflets & Daubechies wavelet.

B. Image Compression Using DWT

In this study, we have examined three types of wavelet families: Daubechies Wavelet, Coiflet Wavelet, and Biorthogonal Wavelet. We have analyzed three different test images: Cell (159X191), Pout (291X240), and Saturn (328X438). Results are measured in terms of Signal to Noise Ratio (SNR), Compression Ratio (CR) and visual quality of compressed image. The comparison of CR & SNR values of wavelets of each wavelet family for different test images shown in figures. Figure 5 shows the Compression Ratio & PSNR value of the cell image similarly Figure 6 & Figure 7 shows the value of CR & PSNR in case of pout and Saturn image. Table 1 shows the different values of CR, PSNR for biorthogonal & Coiflets & Daubechies Wavelet families for cell image. Similarly Table 2 & Table 3 contains the values of CR & PSNR for pout & Saturn image. Biorthogonal has Bior 1.1, bior 1.3, bior 1.5, bior 2.2, bior 2.4, bior 2.6, bior 2.8, bior 3.1, bior 3.3, bior 3.5, bior 3.7, bior 3.9, bior 4.4, bior 5.5 & bior 6.8 wavelet families & coiflets has coi 1, coi 2, coi 3, coi 4 & coi 5. Wavelet families also daubechies wavelet has db 1, db 2, db 4, db 5, db 6, db 8, db 10, db 15, db 16, db 32.




Figure 5. SNR & CR of pout image for Biorthogonal Coiflets & Daubechies wavelet.




Figure 6. SNR & CR of Saturn image for Biorthogonal, Coiflets & Daubechies Wavelet.

TABLE 1: VALUE OF CR, PSNR & SNR OF "CELL IMAGE" USING DIFFERENT WAVELET FAMILIES

S. No.	Biorthogonal				Coiflets				Daubechies			
	Wavelet	CR	PSNR	SNR	Wavelet	CR	PSNR	SNR	Wavelet	CR	PSNR	SNR
1	Bior 1.1	88.7588	33.4990	8.5140	Coi 1	89.7770	33.5960	8.6109	Db 01	88.7588	33.4990	8.5140
2	Bior 1.3	88.8215	33.7365	8.7514	Coi 2	87.9276	33.5865	8.6014	Db 02	88.9964	33.5738	8.5887
3	Bior 1.5	87.6750	33.6707	8.6856	Coi 3	85.5066	33.6689	8.6838	Db 04	87.7697	33.4578	8.4727
4	Bior 2.2	88.3489	34.3007	9.3152	Coi 4	82.9440	33.5380	8.5529	Db 05	85.6539	33.4323	8.4473
5	Bior 2.4	86.5733	34.3598	9.3743	Coi 5	80.8486	33.6334	8.6484	Db 06	84.7630	33.4262	8.4412
6	Bior 2.6	85.9404	34.3915	9.4060					Db 08	81.7179	33.3267	8.3416
7	Bior 2.8	83.4448	34.4005	9.4150					Db 10	77.3059	33.2089	8.2238
8	Bior 3.1	80.7806	34.1836	9.1985					Db 15	70.2901	33.0034	8.0183
9	Bior 3.3	84.0690	34.6726	9.6871					Db 16	68.4673	33.1058	8.1207
10	Bior 3.5	82.6020	34.8046	9.8195					Db 32	52.6860	32.6773	7.6922
11	Bior 3.7	82.9576	34.8186	9.8331								
12	Bior 3.9	77.7927	34.9769	9.9914								
13	Bior 4.4	90.0439	33.4339	8.4488								
14	Bior 5.5	91.3779	32.3524	7.3673								
15	Bior 6.8	86.4629	33.6316	8.6465								

TABLE 2: VALUE OF CR, PSNR & SNR OF "POUT IMAGE" USING DIFFERENT WAVELET FAMILIES

S. No.	Biorthogonal				Coiflets				Daubechies			
	Wavelet	CR	PSNR	SNR	Wavelet	CR	PSNR	SNR	Wavelet	CR	PSNR	SNR
1	Bior 1.1	87.2825	33.9909	13.8298	Coi 1	87.6308	34.482	14.3210	Db 01	87.2825	33.9909	13.8298
2	Bior 1.3	85.4161	34.4734	14.3124	Coi 2	85.8457	34.7469	14.5859	Db 02	88.0164	34.4902	14.3292
3	Bior 1.5	83.7416	34.4565	14.2954	Coi 3	82.8216	34.7311	14.5701	Db 04	86.5505	34.5891	14.4280
4	Bior 2.2	86.873	35.4591	15.2980	Coi 4	78.9678	34.7466	14.5855	Db 05	84.6591	34.561	14.4000
5	Bior 2.4	84.5118	35.7131	15.5520	Coi 5	76.6118	34.7995	14.6385	Db 06	84.1412	34.5494	14.3883
6	Bior 2.6	81.8908	35.8394	15.6784					Db 08	79.8481	34.4311	14.2701
7	Bior 2.8	79.8618	35.9038	15.7428					Db 10	84.6591	34.561	14.4000
8	Bior 3.1	82.6362	35.79	15.6290					Db 15	69.8004	34.3169	14.1559
9	Bior 3.3	82.6989	36.4383	16.2773					Db 16	68.2089	34.3374	14.1763
10	Bior 3.5	79.2208	36.6642	16.5032					Db 32	55.7206	34.0731	13.9120
11	Bior 3.7	77.9105	36.6097	16.4487					Db45	13.6082	6.4504	-13.7107
12	Bior 3.9	74.0749	36.8533	16.6923								
13	Bior 4.4	87.9082	34.3724	14.2113								
14	Bior 5.5	89.5795	33.1339	12.9729								
15	Bior 6.8	83.6676	34.8471	14.6860								

TABLE 3: VALUE OF CR, PSNR & SNR OF "SATURN IMAGE" USING DIFFERENT WAVELET FAMILIES

S. No.	Biorthogonal				Coiflets				Daubechies			
	Wavelet	CR	PSNR	SNR	Wavelet	CR	PSNR	SNR	Wavelet	CR	PSNR	SNR
1	Bior 1.1	86.5844	35.4102	26.8064	Coi 1	90.5244	37.0456	28.1383	Db 01	86.5844	35.4102	26.8064
2	Bior 1.3	86.8167	35.9786	27.3749	Coi 2	91.1516	37.0598	28.456	Db 02	90.3647	36.7295	28.1257
3	Bior 1.5	86.7724	36.0021	27.3984	Coi 3	90.2038	37.1005	28.4968	Db 04	90.6163	36.884	28.2803
4	Bior 2.2	90.5343	38.2953	29.6916	Coi 4	88.3692	37.101	28.5302	Db 05	90.3374	36.9242	28.3204
5	Bior 2.4	90.2474	38.8694	30.2657	Coi 5	86.7603	37.1015	28.4978	Db 06	89.834	36.8352	28.2314
6	Bior 2.6	89.466	39.0122	30.4085					Db 08	88.8889	36.8113	28.2075
7	Bior 2.8	88.4124	39.1934	30.5896					Db 10	87.4486	36.6079	28.0042
8	Bior 3.1	87.655	39.7006	31.0969					Db 15	84.8567	36.2541	27.6504
9	Bior 3.3	88.4202	40.4314	31.8277					Db 16	84.0811	36.209	27.6052
10	Bior 3.5	88.2056	40.8251	32.2213					Db 32	76.5657	35.5105	26.9067
11	Bior 3.7	87.6074	40.9326	32.3289								
12	Bior 3.9	92.4471	36.4811	27.8774								
13	Bior 4.4	86.3357	41.0353	32.4316								
14	Bior 5.5	93.759	34.7608	26.1571								
15	Bior 6.8	90.5895	37.2343	28.6306								

VII. CONCLUSION

This study presented an analysis and comparison of Image Compression using DCT & DWT. In Image Compression using DWT various wavelet families are used for compressing images [12-14].

Image Compression Using DCT depends upon the no of coefficients where higher no of coefficient generate higher signal to noise ratio and image quality. Different images & their coefficient using DCT is also given in its Results.

Image Compression using DWT has various advantages over DCT .In case of image compression DWT no need to divide the input coding into non-overlapping 2-D blocks, it has higher compression ratios avoid blocking artifacts. Also allows good localization both in time and spatial frequency domain. Better identification of which data is relevant to human perception → higher compression ratio

The discrete wavelet transform performs very well in the compression of image signals. The performance measure results are obtained using the Biorthogonal, Coiflets & Daubechies Wavelet Families on to three different images Cell (159X191), Pout (291X240) and Saturn (338X438). The Compression results are measured in terms of CR, SNR. The Experimental results are discussed here for all three images.

CASE -1(Cell image) : In case of Cell image having less pixel size(159X191) bior_2.2 ,Coi_1 & Db_2 provides the better compression ratio, & SNR. However, bior_2.2 is most efficient wavelet family for compressing low resolution images. With Coi_1, compression ratio is higher but SNR is less compared to bior_2.2. Similarly for Db_2, CR high but image quality is low. Among other wavelets Coi_1and bior_3.3 gives high SNR but Compression Ratio achieved is comparatively low.

CASE-2(Pout Image): For medium pixel size images such as pout (291X240) bior_2.2. , Coi_1 & Db_2 provides better results as is the case for low pixel size Cell image.

CASE-3(Saturn image): For high pixel size images such as Saturn (338X438) Coi_2 provides better Compression ratio as compared to the biorthogonal & Daubechies families. Bior_2.2 & Db_2 also provides good compression ratio but comparatively less than Coi_2.

Finally, it can concluded that for low pixel size image biorthogonal wavelet is best among all the families and for high pixel size image coiflets is better suited. In case of medium size images, both daubechies & biorthogonal provides better results. Simulation results prove the effectiveness of DWT based techniques in attaining an efficient compression ratio, achieving higher signal to noise ratio and better peak signal to noise ratio (PSNR), while the retained signal energy is 99.94% and image quality is much smoother. Biorthogonal has the highest compression ratio & signal to noise ratio. Results are also tested through the wavelet toolbox which has given the higher energy ratio. As wavelet image compression has revolutionized image

compression field with unbelievable results. This involves the state of art techniques but wavelet decomposition remains the initial step for all these including wavelet packets techniques. Therefore there was a need to exploit the inherent ability of wavelets.

VIII. REFERENCES

- [1] J.D.Gibson, T. Berger, T. Lookbaugh, D. Linghergh and R.L. Baker, Digital Compression for Multimedia, Morgan Kaufmann 1998.
- [2] Yogendra Kumar Jain & Sanjeev Jain "Performance Analysis and Comparison of Wavelet Families Using for the image compression". International Journal of soft Computing2 (1):161-171, 2007
- [3] Yogendra Kumar Jain & Sanjeev Jain "Performance Evaluation of Wavelets for Image Compression". International Journal of soft Computing2 (1):1104-112, 2006
- [4] Sonja Grgic, Mislav Grgic, Member IEEE, and Branka Zovko-Cihlar, Member IEEE, "Performance Analysis of Image Compression Using Wavelets" IEEE TRANSACTIONS ON INDUSTRIAL ELECTRONICS, VOL. 48, NO. 3, JUNE 2001
- [5] Digital Compression and Coding of Continuous Tone Still Images, 1991. ISO/IEC IS 10918.
- [6] Information Technology-Coding of moving pictures and associated audio for digital storage media at up to about 1.5 Mb/s: Video, ISO/IEC IS 11172.
- [7] Information Technology-Generic Coding of Moving Pictures and Associated Audio Information, Video, ISO/IEC IS 13818, 1994.
- [8] Rao, K.R. and P. Yip, Discrete cosine transform: Algorithms, Advantages and Applications, San Diego, CA: Academic 1990.
- [9] Bauer, S., B. Zovko-Cihlar and M. Grgic, The influence of impairments from digital compression of video signal on perceived picture quality, Proc. 3rd Intl. Workshop Image and Signal Processing, IWISP'96, Manchester, U.K., pp: 245-248 1996.
- [10] M. Vetterli, J. Kovacevic, Wavelets and sub band coding, 1st (Edn.), Prentice-Hall, Englewood Cliffs, NJ 1995.
- [11] DeVore, R.A. B. Jawerth, B. Lucier, Image compression through wavelet transforms coding, IEEE Trans. Info. Theory, 38: 719-746 1992.
- [12] S. Cabrera, V. Kreinovich and O. Sirisaengtaksin, Wavelets compress better than all other methods: A 1-dimensional theorem, Technical Report 25, University of Texas at El Paso, El Paso, TX 79968.
- [13] Wallace, the JPEG still picture compression standard, IEEE Trans. Consumer Electronics, 1992.
- [14] X. Zixiang., K. Ramchandran, M.T. Orchard and Y.Q. Zhang, A comparative study of DCT- and wavelet-based image coding, IEEE Trans. Circuits Syst. Video Technol., pp: 692-695 1999.